

Victorian II Pole

The fluted Victorian pole features neoclassical detailing that complements many period architectural styles, yet blends easily with more modern surroundings. The slightly tapered shaft lends a graceful look to this elegant Victorian.

Our Victorian Series lighting poles combine the charm of yesterday with the technology of today. Available in a variety of configurations, colors and finishes, the Victorian series provides architects and designers with many creative options.

Durability with a classic touch.

Available in base plate and embedded styles.

Features and Benefits

- Prestressed steel and highest quality concrete are centrifugally cast for ultimate strength and long-term durability
- Natural stone and terrazzo aggregates maintain a like new appearance with virtually no maintenance
- Conforms to applicable sections of ACI, AASHTO, ASTM and PCI standards
- Exclusive 10-year warranty

Colors and Finishes

A wide range of standard, pre-formulated and custom colors are available. The concrete shafts are lightly blasted to expose the texture and beauty of the natural stone. See separate Aggregates and Finishes sheet for details. We offer Amerishield[™], a premium graffiti-resistant coating, as well as other durable sealers and protectants that further enhance colors, protect the concrete surface and aid in the removal of graffiti.



6

Victorian II - Base plate style information

Catalog	Pole	Base	Anchor	Bolt	Base	Ultimate	Pole
Number	Height "A"	OD	Bolt	Circle	Plate (Sq)	G.L. Moment	Weight
VBF03.1	10'-2"	13 "	3/4" x 24"x 4"	16"	14"	12,000ft·lbs	350lbs
VBF03.7*	12'-2"	13 "	3/4" x 24"x 4"	16 "	14"	12,000ft·lbs	375 lbs
VBF04.1	13' -5"	13 "	3/4" x 24"x 4"	16 "	14"	12,000ft·lbs	400lbs
VBF04.7*	15' -5"	13 "	3/4" x 24"x 4"	16 "	14"	15,000ft·lbs	500lbs
VBF04.8	15' -5"	13 "	3/4" x 24"x 4"	16 "	14"	15,000ft·lbs	500lbs
VBF05.6	18'-4"	16"	3/4" x 24"x 4"	19"	17 "	15,000ft·lbs	700lbs
VBF06.2*	20'-4"	16 "	3/4" x 24"x 4"	19"	17 "	17,000ft·lbs	800lbs

Victorian II - Embedded style information


Catalog Number	Pole Height "A"	Base OD	Embedded Depth "B"	Overall Length "OL"	Ultimate G.L. Moment	Pole Weight
VEF03	9'-10"	13 "	3'-3"	13'-1"	12,000ft·lbs	475lbs
VEF03.6*	11'-10"	13 "	3'-3"	15' -1"	12,000ft·lbs	500lbs
VEF04.0	13'-0"	13 "	4'-3"	17'-3"	12,000ft·lbs	575 lbs
VEF04.6*	15'-0"	13 "	4'-3"	19'-3"	15,000ft·lbs	725 lbs
VEF04.8	15'-0"	13 "	4'-3"	19'-3"	15,000ft·lbs	725 lbs
VEF05.5	18'-0"	16"	4'-11"	22'-11 "	15,000ft·lbs	760lbs
VEF06.1*	20'-0"	16"	4'-11"	24'-11 "	17,000ft·lbs	860lbs

*VEF03.6. VEF04.6, VEF06.1, VBF03.7, VBF04.7, and VBF06.2: Top 28" of pole is 5^{1/8}" round not fluted.




Shaft cross section detail

Specifications - Use Centrecon specifications



Slotted base plate prestressed to pole



5^{1/8"} top OD "A' "OL" Ground line -Double "B" cable entrances

7

Colors and finishes - See Centrecon color selection guide Luminaire mounting - See mounting options section for more information Anti-graffiti and sealer - Optional coatings are available for added protection

